

SAFETY DATA SHEET

This form is regarded to be in compliance with 29 CFR Part 1910.1200

Section 1: Identification

Product Name: Chip Resistant Base Coat **DATE:** 6/16/16
Product N°: BASE 5500 (RB702)
Product Class: Nail Polish
Manufactured by: ILabs LLC, 12330 McCann Drive Santa Fe Spring, CA 90670 USA
Telephone: (714) 375-2599 **Fax No:** (714) 375-2596
Emergency: 1 800 656-2646

Section 2: Hazard(s) Identification

• DESIGNATION OF HAZARD

FLAMMABLE

Vapours form from this product and may travel or be moved by air currents and ignited by pilot lights, other flames, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point. This material may produce a floating fire hazard.

• EFFECTS OF OVEREXPOSURE

Cause eye irritation. Harmful if swallowed. May cause nose and throat irritation. Causes skin irritation. May effect the brain or nervous system, causing dizziness, headache or nausea. Harmful if inhaled.

• OTHER EFFECTS OF OVEREXPOSURE MAY INCLUDE

Narcosis, conjunctivitis, loss of coordination, vomiting, lacrimation, redness and swelling of eyes, difficulty with speech, reduced visibility, abdominal pain, swelling and redness of skin, fatigue, cough, dermatitis, drowsiness, unconsciousness.

• PRIMARY ROUTE(S) OF ENTRY

Inhalation, skin contact, eyes.

• MEDICAL CONDITIONS THAT CAN BE AGGRAVATED

NA

• CHRONIC HEALTH HAZARDS

• REPEATED OVEREXPOSURE TO THIS PRODUCT MAY CAUSE

Lung damage, liver anomalies, kidney damage, central nervous system damage, blood effects.

In accordance with 29CFR1910.1200, this product contains no ingredients listed by NTP, IARC or OSHA as carcinogenic.

• NOTICE

Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents of this package may be harmful or fatal.

Section 3: Composition/Information on Ingredients

• CHEMICAL CHARACTERIZATION

Nitrocellulose with nitrogen content < 12.2 % and at a concentration < 20 % in a blend of solvents.

• HAZARDOUS COMPONENTS

INGREDIENT	CAS NUMBER	HAZARD	HAZARD SYMBOL
ISOPROPYL ALCOHOL	67 - 63 - 0	HIGHLY FLAMMABLE IRRITANT	F, Xi
ETHYL ACETATE	141 - 78 - 6	HIGHLY FLAMMABLE IRRITANT	F, Xi
BUTYL ACETATE	123 - 86 - 4	FLAMMABLE	—
NITROCELLULOSE	9004 - 70 - 0	HIGHLY FLAMMABLE	F

SAFETY DATA SHEET

This form is regarded to be in compliance with 29 CFR Part 1910.1200

Section 4: First-Aid Measures

• SKIN CONTACT

Remove contaminated clothing and wash before reuse. Remove and destroy contaminated shoes. Flush with plenty of water.

• INHALATION

Remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Get medical attention.

• INGESTION

Get medical attention **IMMEDIATELY**.

• EYE CONTACT

Immediately wash the eyes with plenty of water for a least 10 mn holding the eye open. Obtain medical attention urgently.

Section 5: Fire-Fighting Measures

• EXTINGUISHING MEDIA

Foam, Carbon Dioxide or Dry Chemical.

• UNUSUAL FIRE AND EXPLOSION HAZARD

During emergency conditions, overexposure to decomposition products may cause a health hazard; symptoms may not be immediately apparent. Obtain medical attention.

• SPECIAL FIREFIGHTING PROCEDURES

Water may be ineffective in fighting fire. If water is used to cool closed containers to prevent pressure build-up, fog nozzles are preferred. Full protective equipment, including self-contained breathing apparatus is needed to protect firefighters from exposure to coating's hazardous ingredients and hazardous decomposition products.

Section 6: Accidental Release Measures

• STEP TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Remove all sources of ignition. Wear appropriate safety equipment as listed in Section 8. Absorb on inert material and dispose of as below.

• WASTE DISPOSAL METHODS

Dispose in accordance with FEDERAL, STATE and local regulations. Incineration is the preferred method of disposal.

Section 7: Handling and Storage

• PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Store in well-ventilated area. Keep containers closed when not in use. Store away from ignition sources. All equipment should be grounded. Avoid strong oxidizing agents, store in a clean, dry area.

• OTHER PRECAUTIONS

All precautions must be observed. Empty container may retain product residues (vapour or liquid).

SAFETY DATA SHEET

This form is regarded to be in compliance with 29 CFR Part 1910.1200

Section 8: Exposure Controls/Personal Protection

• EXPOSURE LIMITS

Hazardous Ingredients	Cas N°	Desc.	Value	Unit	Comment
BUTYL ACETATE <Acetic Acid, Butyl Ester>	123-86-4	PEL-TWA	150	ppm	
		TLV-STEL	200	ppm	15 minutes
		PEL-STEL	200	ppm	15 minutes
NITROCELLULOSE <GUN CQ.U.:QN>	9004-70-0	PEL-TWA	NA		
ETHYL ACETATE	141-78-6	PEL-TWA	400	ppm	
ISOPROPANOL <ISOPROPYL ALCOHOL> <ISOPROPYL ALCOHOL>	67-63-0	PEL-TWA	400	ppm	
		TLV-STEL	500	ppm	15 minutes
		PEL-STEL	500	ppm	15 minutes

• PERSONAL PROTECTION

RESPIRATORY PROTECTION

Wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during application and handling unless air monitoring demonstrates vapour /mist levels below applicable limits. Follow respirator manufacturer's recommendations for selection and use.

VENTILATION

Sufficient ventilation must be provided to maintain airborne concentrations below TLV, PEL and LEL Limits as listed in Section 8.

PROTECTIVE GLOVES

Chemical resistant protective gloves should be worn when handling this product. Check with glove manufacturer to determine proper glove type

EYE PROTECTION

Splash-proof chemical goggles should be worn.

OTHER PROTECTIVE EQUIPMENT

Impervious clothing and boots should be worn. Eye bath and safety shower should be provided.

HYGIENIC PRACTICES

Good personal hygiene practices are required at all times when handling chemicals. These practices include, but are not limited to, washing when safety equipment is removed, at the end of each shift or when going on breaks and especially if contamination occurs.

Section 9: Physical and Chemical Properties

FORM	: Viscous liquid	
COLOUR	: Depend of the reference	
ODOUR	: Esters	
BOILING POINT	: 77°C at 1013 hPa (Ethyl Acetate)	
BOILING RANGE	: 77 at 130°C	
SPECIFIC GRAVITY	: >1.000	
VAPOUR PRESSURE (mm Hg)	: 100 (27°C) (Ethyl Acetate)	
FLASH POINT	: <21°C	
FLAMMABLE LIMITS (% v/v)	: <u>Upper</u>	<u>Lower</u>
Ethyl Acetate	11.0	2.2
Butyl Acetate	7.6	1.7
Isopropanol	12.0	1.8
pH	: Not applicable	
SOLUBILITY IN WATER	: Insoluble	
EVAPORATION RATE	: Slower than ether	

SAFETY DATA SHEET

This form is regarded to be in compliance with 29 CFR Part 1910.1200

Section 10: Stability and Reactivity

Material is **STABLE** under non-emergency conditions.

Material **WILL NOT** undergo hazardous polymerization.

HAZARDOUS DECOMPOSITION PRODUCTS

Methane, oxides of nitrogen. Carboxylic acids, various hydrocarbons, oxides of carbon, aldehydes, hydrogen cyanide, acids.

CONDITIONS TO AVOID

Heat, sparks, open flame.

MATERIALS TO AVOID

Sodium hydroxyde, nitric acid, oxidizers, acids, alkali, metal, amines.

Section 11: Toxicological Information

INGREDIENT	LD50 (Oral, Rat)	LC50 (Inhal, Rat)	LC50 (Dermal, Rabbit)
ETHYL ACETATE	11300 mg/Kg	1600 ppm (8h)	
BUTYL ACETATE	14000 mg/Kg	2000 ppm	
ISOPROPYL ALCOHOL	5840 mg/Kg	16000 ppm (8h)	13000 mg/Kg

INGESTION

Important ingestion can cause nausea and a great narcosis with weakness, drowsiness and loss of consciousness.

INHALATION

Can cause irritation of the nose and the throat. At high concentration can cause narcosis.

CONTACT WITH THE SKIN

Prolonged contact can cause crack in skin.

CONTACT WITH THE EYES

Can cause irritation of the conjunctive. Can cause injury of the cornea

Section 12: Ecological Information

No DATA

Section 13: Disposal Considerations

ROAD TRANSPORT

Technical name : PAINT (Source of danger: Ethyl acetate, Butyl acetate, Nitrocellulose, Isopropyl alcohol)
 ADR Class : 3
 ADR Pack group : II
 Danger label : 3
 Kemler number : 33
 UN Number : 1263

MARITIME TRANSPORT

Technical name : PAINT (Source of danger: Ethyl acetate, Butyl acetate, Nitrocellulose, Isopropyl alcohol)
 UN Number IMDG : 1263
 Class Marine : 3
 pollutant Ems : No
 Number IMDG : F-E, S-E
 Pack Group : II
 Danger label : 3
 Flash point : -5°C

SAFETY DATA SHEET

This form is regarded to be in compliance with 29 CFR Part 1910.1200

Other indications relative to maritime transport:

:Not viscous product as per IMDG code 2.3.2.5

-Limited Quantity: 51/30kg (gross)

-Certified packaging: Internal packaging metal, glass, plastic
External packaging: Carton 4G

IATA

Technical name	: PAINT (Source of danger: Ethyl acetate, Butyl acetate, Nitrocellulose, Isopropyl alcohol)
UN Number	: 1263
IATA Class	: 3
Danger label	: 3
Pack Group	: II
Packing instr	: 305(Passenger) - Maximum Quantity 51 30 Car o - Maximum Quanti 601

Section 14: Transport Information

No DATA

Section 15: Regulatory Information

Labelling according to EEC-Directives

SYMBOL	: F, Xi
INDICATION OF DANGER	: Highly Flammable, Irritant
RISK PHRASES	:11, 36, 66, 67
SAFETY PHRASES	:16,26,33

Section 16: Other Information

DISCLAIMER

While ILabs LLC, believes that the data contained herein are accurate and derived from qualified sources, the data are not to be taken as a warranty or representation for which ILabs LLC, assumes legal responsibility. They are offered solely for your consideration, investigation and verification. Any use of these data information must be determined by the user to be in accordance with applicable Federal, state and local laws regulations. ILabs LLC, requires all Customer who receive this Security Data Record to study it carsfully in order to be informed of any dangers presented by the product. As far as security is concerned, the Customer should :

- 0 Inform his employees, agents and sub-contractors of information contained in this form.
- 0 Supply one copy of this form to each one of his own Customers for this product.
- 0 Ask for these same Customers to inform in turn their own Employees and Customers.