

SAFETY DATA SHEET

This form is regarded to be in compliance with 29 CFR Part 1910.1200

Section 1: Identification

Product Name: Top Coat Color Sealer

DATE: 6/16/16

HMIS Codes: H F R P

Series: 2504

1 3 0 G

Product Class: Nail Polish

Manufactured by: ILabs LLC, 12330 McCann Drive Santa Fe Spring, CA 90670 USA

Telephone: (714) 375-2599 **Fax No:** (714) 375-2596

Emergency: 1 800 656-2646

Section 2: Hazard(s) Identification

• INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Vapors may be irritating and cause dizziness, headache, nausea, vomiting and narcosis

• SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

Brief contact with skin should no produce any harmful effects, but prolonged contact, as from clothing wet with chemicals, may cause irritation. Eye contact causes severe irritation.

• INGESTION HEATH RISKS AND SYMPTOMS OF EXPOSURE

May cause toxicological and neurological effects.

• HEALTH HAZARDS (ACUTE AND CHRONIC)

Acute ingestion can cause headache, drowsiness and unconsciousness, acute inhalation of vapors are irritating to nasal passages and throat. Acute repeated or prolonged skin contact can cause drying of the skin, and acute vapor or liquid ma be harmful to the eyes.

• CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

Emphysema, Asthma, Dermatitis.

Section 3: Composition/Information on Ingredients

• CHEMICAL CHARACTERIZATION

Nitrocellulose with nitrogen content < 12.2 % and at a concentration < 20 % in a blend of solvents.

• HAZARDOUS COMPONENTS

INGREDIENT	CAS NUMBER	OHSA PEL	ACGIH TWA	TLV STEL	WEIGHT%
CAMPHOR	76 - 22 - 2	2MG/M3	2PPm	2PPM	0.1 - 2
ETHYL ACETATE	141 - 78 - 6	400PPM	400PPm	200PPM	35 - 45
ISOPROPYL ALCOHOL	67 - 63 - 4	400PPM	400PPM	500PPM	15 - 25
N-BUTYL ACETATE	123 - 86 - 4	150PPM	150PPM	200PPM	20 - 30
NITROCELLULOSE	9004 - 70 - 0	400PPM	NA	NA	0 - 5

SAFETY DATA SHEET

This form is regarded to be in compliance with 29 CFR Part 1910.1200

Section 4: First-Aid Measures

• INHALATION (BREATHING)

If symptoms of exposure develop (see Section 5), move victim away from source of exposure and into fresh air. If symptoms persist, seek immediate medical attention. If victim is not breathing, artificial respiration should be administered by qualified personnel. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.

• INGESTION- (SWALLOWING)

Seek medical attention, if victim is drowsy or unconscious, place on left side with head down. Do not give anything by mouth. If victim is conscious and alert, vomiting should be induced for ingestion of large amounts (more than 5 ounces in an adult) preferably with syrup of ipecac under direction from a physician or poison center. If syrup of ipecac is not available, vomiting can be induced by giving 3 tablespoons of liquid dishwashing soap in a glass of water, or by gently placing 2 fingers in the back of the throat. If possible do not leave the victim unattended. Seek medical attention.

• EYE CONTACT

Move victim away from exposure to vapors and into fresh air. If irritation or redness develops, seek medical attention. For direct contact flush the effected eye with clean water for at least 15 minutes. Seek medical attention.

• SKIN CONTACT

Remove all contaminated clothing. Cleanse affected areas thoroughly by washing with mild soap and water. If irritation or redness develops and persists, seek medical attention.

• IF SWALLOWED CALL A PHYSICIAN/SKIN

Flush with water. If inhaled remove to fresh air and call a physician, give artificial respiration if breathing is difficult. Eyes - flush with plenty of water at least 15 minutes. Treatment should be directed at the control of symptoms and the clinical conditions, there is no specific antidote.

Section 5: Fire-Fighting Measures

• EXTINGUISHING MEDIA

Foam, Alcohol Foam, Co2, Dry Chemical, Large Volume Water Fog

• UNUSUAL FIRE AND EXPLOSION HAZARD

Avoid unnecessary exposure to heat. Vapors may travel to source

• SPECIAL FIREFIGHTING PROCEDURES

Materials burn rapidly with intense heat, use self-contained breathing apparatus and protective clothing. Fight fire from a distance due to the threat of pressures in containers which can cause an explosion.

Section 6: Accidental Release Measures

• STEP TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Wear suitable protective equipment. Spills should be collected for disposal by appropriate methods. For large spills in excess of R.Q. reportable quantities contact national response center at 800-424-8802

Section 7: Handling and Storage

• PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Store large quantities only in buildings designed to comply with osha 1910.106. Store in cool area.

• OTHER PRECAUTIONS

Keep closure tight and container upright to prevent leakage. Do not store or use heat, sparks or open flame. Store drum out of sun and away from heat. Store and use only in well-ventilated areas. Drums of this material should be grounded when pouring. Never use pressure to empty. Drum is not a pressure vessel. Do not puncture container or leave opened or uncovered. Drums should not be washed out or used for their purposes. Do not get in eyes, avoid skin contact. Harmful if inhaled. Prevent prolonged or repeated breathing of vapor or mist. Read instructions before using.

SAFETY DATA SHEET

This form is regarded to be in compliance with 29 CFR Part 1910.1200

Section 11: Toxicological Information

ACUTE EXPOSURE

Oral toxicity- the LD50 in rate is between 20000 mg/kg and 5000mg/kg. Based on data of similar materials. Swallowing this material causes irritate of mouth, esophagus and stomach, with nausea, vomiting, diarrhea and abdominal pain. Material can be aspirated into the lungs during the act of swallowing or vomiting. This could result in pulmonary edema and chemical pneumonitis.

EYE IRRITATION

Moderate to strong eye irritation. Based on data from components or similar material.

SKIN IRRITATION

May cause skin irritation, based on data from components or similar materials.

DERMAL TOXICITY

Based on data from components

INHALATION TOXICITY

High concentration may cause headache, dizziness, nausea, stupor and other central nervous system effects leading to visual impairment, difficulty breathing and convulsions.

RESPIRATORY IRRITATION

Nose, Throat and Lung irritant. Based on data from components or similar material.

Section 12: Ecological Information

FRESHWATER FISH TOXICITY: Not Determined

FRESHWATER INVERTEBRATES TOXICITY: Not Determined

ALGAL INHIBITION: Not Determined

SALTWATER FISH TOXICITY: Not Determined

BACTERIA TOXICITY: Not Determined

Section 13: Disposal Considerations

WASTE DISPOSAL METHOD

Dispose of waste by appropriate methods or incinerate in a furnace where permitted under appropriate federal, state and local regulations.

Section 14: Transport Information

PROPER SHIPPING NAME: Paint

DOT HAZARDOUS CLASS: 3 (Flammable Liquid)

PACKAGING GROUP: PGII

UN ID NUMBER: 1263

MARINE POLLUTANT

Section 15: Regulatory Information

No Data

SAFETY DATA SHEET

This form is regarded to be in compliance with 29 CFR Part 1910.1200

Section 16: Other Information

HMIS CODES

HEALTH - 1

FIRE - 3

REACTIVITY - 0

SPECIAL - G

DISCLAIMER

While ILabs LLC, believes that the data contained herein are accurate and derived from qualified sources, the data are not to be taken as a warranty or representation for which ILabs LLC, assumes legal responsibility. They are offered solely for your consideration, investigation and verification. Any use of these data information must be determined by the user to be in accordance with applicable Federal, state and local laws regulations. ILabs LLC, requires all Customer who receive this Security Data Record to study it carefully in order to be informed of any dangers presented by the product. As far as security is concerned, the Customer should :

- 0 Inform his employees, agents and sub-contractors of information contained in this form.
- 0 Supply one copy of this form to each one of his own Customers for this product.
- 0 Ask for these same Customers to inform in turn their own Employees and Customers.