

# Safety Data Sheet



Revision Number: 007.0

Issue date: 09/07/2022

## 1. PRODUCT AND COMPANY IDENTIFICATION

**Product name:** Quad Max Window, Door and Siding Sealant  
**IDH number:** 2622496  
**Product type/use:** Joint sealant, polymer silan-modified  
**Restriction of Use:** None identified  
**Region:** United States  
**Company address:** Henkel Corporation  
One Henkel Way  
Rocky Hill, Connecticut 06067  
**Contact information:**  
Telephone: +1 (860) 571-5100  
MEDICAL EMERGENCY Phone: Poison Control Center  
1-877-671-4608 (toll free) or 1-303-592-1711  
TRANSPORT EMERGENCY Phone: CHEMTREC  
1-800-424-9300 (toll free) or 1-703-527-3887  
Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**WARNING:** CAUSES SKIN IRRITATION.  
CAUSES SERIOUS EYE IRRITATION.

| HAZARD CLASS    | HAZARD CATEGORY |
|-----------------|-----------------|
| SKIN IRRITATION | 2               |
| EYE IRRITATION  | 2A              |

### PICTOGRAM(S)



### Precautionary Statements

**Prevention:** Wash affected area thoroughly after handling. Wear protective gloves, eye protection, and face protection.  
**Response:** IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.  
**Storage:** Not prescribed  
**Disposal:** Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s)                                 | CAS Number  | Percentage* |
|--|-------------|-------------|
| Limestone  | 1317-65-3   | 50 - 60     |
| Phthalic acid, di(C9-11)alkylester, branched, C10-rich | 68515-49-1  | 5 - 10      |
| Benzene, mono-C10-13-alkyl derivs.                     | 129813-58-7 | 1 - 5       |
| Trimethoxyvinylsilane                                  | 2768-02-7   | 1 - 5       |
| Benzene, mono-C12-14-alkyl derivs.                     | 129813-59-8 | 1 - 5       |
| Quartz (SiO <sub>2</sub> )                             | 14808-60-7  | 0.1 - 1     |

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

IDH number: 2622496

Product name: Quad Max Window, Door and Siding Sealant

Exposure to moisture during cure will release 0.1 - 0.9% methanol.

#### 4. FIRST AID MEASURES

|                      |   |
|----------------------|---|
| <b>Inhalation:</b>   | Move to fresh air. If symptoms persist, seek medical advice.  |
| <b>Skin contact:</b> | Wash with soap and water. If skin irritation persists, call a physician. Wipe off paste with paper towel or cloth.  |
| <b>Eye contact:</b>  | Flush with copious amounts of water, preferably, lukewarm water for at least 15 minutes, holding eyelids open all the time. If symptoms develop and persist, get medical attention. |
| <b>Ingestion:</b>    | Do not induce vomiting. If a person feels unwell or symptoms of skin irritation appear, consult a physician.  |
| <b>Symptoms:</b>     | See Section 11.   |

#### 5. FIRE FIGHTING MEASURES

|   |  |
|---|--|
| <b>Extinguishing media:</b>               | carbon dioxide, foam, powder, water spray jet, fine water spray  |
| <b>Special firefighting procedures:</b>   | Wear protective equipment. Wear self-contained breathing apparatus.  |
| <b>Unusual fire or explosion hazards:</b> | None identified.   |
| <b>Hazardous combustion products:</b>     | Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. |

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

|                                   |  |
|-----------------------------------|--|
| <b>Environmental precautions:</b> | Do not allow product to enter sewer or waterways.  |
| <b>Clean-up methods:</b>          | Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Store in a partly filled, closed container until disposal. Spilled material will solidify. Scrape up as much material as possible. Maintain good ventilation for large spills. |

#### 7. HANDLING AND STORAGE

|                  |   |
|------------------|---|
| <b>Handling:</b> | Do not handle contact lenses until all sealant has been removed from hands. Residual sealant may transfer to lenses and cause eye irritation. Avoid contact with eyes, skin and clothing. Keep out of the reach of children. Protect from moisture. Use only with adequate ventilation. |
| <b>Storage:</b>  | For safe storage, store between -20 °C (-4°F) and 50 °C (122°F) Store in a cool, dry area. Avoid moisture.  |

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)                                 | ACGIH TLV   | OSHA PEL  | AIHA WEEL | OTHER |
|--|---|---|-----------|-------|
| Limestone  | 10 mg/m3 TWA<br>Inhalable particles.<br>3 mg/m3 TWA<br>Respirable particles.<br>10 mg/m3 TWA Total<br>dust. | 5 mg/m3 PEL<br>Respirable fraction.<br>15 mg/m3 PEL Total<br>dust.<br>5 mg/m3 TWA<br>Respirable fraction.<br>50 MPPCF TWA<br>Total dust.<br>15 mg/m3 TWA Total<br>dust.<br>15 MPPCF TWA<br>Respirable fraction.   | None      | None  |
| Phthalic acid, di(C9-11)alkylester, branched, C10-rich | None  | None  | None      | None  |
| Benzene, mono-C10-13-alkyl derivs.                     | None  | None  | None      | None  |
| Trimethoxyvinylsilane                                  | None  | None  | None      | None  |
| Benzene, mono-C12-14-alkyl derivs.                     | None  | None  | None      | None  |
| Quartz (SiO <sub>2</sub> )                             | 0.025 mg/m3 TWA<br>Respirable fraction.   | 0.05 mg/m3 TWA<br>(Respirable dust.)<br>(Respirable dust.)<br>0.025 mg/m3<br>OSHA_ACT<br>(Respirable dust.)<br>0.05 mg/m3 PEL<br>Respirable dust.<br>2.4 MPPCF TWA<br>Respirable.<br>0.1 mg/m3 TWA<br>Respirable. | None      | None  |

**Engineering controls:**

Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination below occupational exposure limits.

**Respiratory protection:**

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Eye/face protection:**

Safety goggles or safety glasses with side shields.

**Skin protection:**

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|   |   |
|---|---|
| <b>Physical state:</b>                          | Liquid  |
| <b>Color:</b>                                   | Various   |
| <b>Odor:</b>                                    | Alcohol   |
| <b>Odor threshold:</b>                          | Not available.  |
| <b>pH:</b>                                      | Not applicable  |
| <b>Vapor pressure:</b>                          | Not applicable  |
| <b>Boiling point/range:</b>                     | Not applicable  |
| <b>Melting point/ range:</b>                    | Not applicable  |
| <b>Specific gravity:</b>                        | 1.4 - 1.5 at 20 °C (68°F)   |
| <b>Vapor density:</b>                           | Heavier than air.   |
| <b>Flash point:</b>                             | 107 °C (224.6 °F) Seta closed cup   |
| <b>Flammable/Explosive limits - lower:</b>      | Not available.  |
| <b>Flammable/Explosive limits - upper:</b>      | Not available.  |
| <b>Autoignition temperature:</b>                | Not applicable  |
| <b>Flammability:</b>                            | Not applicable  |
| <b>Evaporation rate:</b>                        | Not applicable  |
| <b>Solubility in water:</b>                     | Insoluble   |
| <b>Partition coefficient (n-octanol/water):</b> | Not available.  |
| <b>VOC content:</b>                             | 2.48 %; 36 g/l (by weight, calculated using CARB method; g/L less water, less exempts calculated using SCAQMD method) |
| <b>Viscosity:</b>                               | Not available.  |
| <b>Decomposition temperature:</b>               | Not available.  |

IDH number: 2622496

Product name: Quad Max Window, Door and Siding Sealant

## 10. STABILITY AND REACTIVITY

|  |   |
|--|---|
| <b>Stability:</b>                        | Stable under normal conditions of storage and use.      |
| <b>Hazardous reactions:</b>              | Will not occur.   |
| <b>Hazardous decomposition products:</b> | Methanol is liberated slowly upon exposure to moisture. |
| <b>Incompatible materials:</b>           | Oxidizing agents.                                       |
| <b>Reactivity:</b>                       | Not available.  |
| <b>Conditions to avoid:</b>              | Exposure to moisture.                                   |

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Skin, Inhalation, Eyes, Ingestion

### Potential Health Effects/Symptoms

|                      |  |
|----------------------|--|
| <b>Inhalation:</b>   | May cause nose, throat and lung irritation. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release. |
| <b>Skin contact:</b> | Causes skin irritation.  |
| <b>Eye contact:</b>  | Causes serious eye irritation.   |
| <b>Ingestion:</b>    | May be harmful if swallowed.   |

**Acute inhalation product toxicity:** The substance or mixture has no acute inhalation toxicity.

| Hazardous Component(s)                                 | LD50s and LC50s                       | Immediate and Delayed Health Effects                  |
|--|---------------------------------------|---|
| Limestone  | None                                  | Nuisance dust   |
| Phthalic acid, di(C9-11)alkylester, branched, C10-rich | None                                  | Irritant  |
| Benzene, mono-C10-13-alkyl derivs.                     | None                                  | No Data   |
| Trimethoxyvinylsilane                                  | Inhalation LC50 (Rat, 4 h) = 2773 ppm | Irritant, Allergen                                    |
| Benzene, mono-C12-14-alkyl derivs.                     | None                                  | No Data   |
| Quartz (SiO <sub>2</sub> )                             | None                                  | Immune system, Lung, Some evidence of carcinogenicity |

| Hazardous Component(s)                                 | NTP Carcinogen                | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|--|-------------------------------|-----------------|--|
| Limestone  | No                            | No              | No                                       |
| Phthalic acid, di(C9-11)alkylester, branched, C10-rich | No                            | No              | No                                       |
| Benzene, mono-C10-13-alkyl derivs.                     | No                            | No              | No                                       |
| Trimethoxyvinylsilane                                  | No                            | No              | No                                       |
| Benzene, mono-C12-14-alkyl derivs.                     | No                            | No              | No                                       |
| Quartz (SiO <sub>2</sub> )                             | Known To Be Human Carcinogen. | Group 1         | Yes                                      |

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

|                                  |               |
|----------------------------------|---------------|
| <b>Proper shipping name:</b>     | Not regulated |
| <b>Hazard class or division:</b> | None          |
| <b>Identification number:</b>    | None          |
| <b>Packing group:</b>            | None          |

### International Air Transportation (ICAO/IATA)

|                                  |               |
|----------------------------------|---------------|
| <b>Proper shipping name:</b>     | Not regulated |
| <b>Hazard class or division:</b> | None          |
| <b>Identification number:</b>    | None          |
| <b>Packing group:</b>            | None          |

### Water Transportation (IMO/IMDG)

|                                  |               |
|----------------------------------|---------------|
| <b>Proper shipping name:</b>     | Not regulated |
| <b>Hazard class or division:</b> | None          |
| <b>Identification number:</b>    | None          |
| <b>Packing group:</b>            | None          |

## 15. REGULATORY INFORMATION

### United States Regulatory Information

**TSCA 8 (b) Inventory Status:** All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.

**TSCA 12 (b) Export Notification:** None above reporting de minimis

**CERCLA/SARA Section 302 EHS:** None above reporting de minimis.

**CERCLA/SARA Section 311/312:** Delayed Health, Immediate Health

**CERCLA/SARA Section 313:** None above reporting de minimis.

**California Proposition 65:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. This product contains a chemical known in the State of California to cause cancer.

### Canada Regulatory Information

**CEPA DSL/NDSL Status:** Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

## 16. OTHER INFORMATION

**This safety data sheet contains changes from the previous version in sections:** This Safety Data Sheet contains changes from the previous version in Section(s): 3, 8, 11, 13

**Prepared by:** Product Safety and Regulatory Affairs

**Issue date:** 09/07/2022

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.