



PRODUCT SPECIFICATIONS For 9" Logs

Description: Air-dried white pine, 9" diameter log.

Size: Available in even lengths only, 6 feet to 20 feet in length.

Details: As a member of the log home council all logs are inspected and graded according to their specifications and regulations. All full log products may naturally check or crack. These cracks are an unavoidable process and will enhance the natural beauty and appearance.

Coverage: 1.5 lineal feet = 1 square foot. Coped logs will have an 8 inch stack height.

Fasteners: 10-12" log screws are recommended.

Corners: Full Tail Saddle Notched Corners are available for 9" coped logs. No tails are available for full round 9" logs.

Ground Contact: It is not recommended for logs to be in direct contact with the ground or in damp locations. If stacking logs for a home, the foundation should be at least 16 inches above grade and the home should have at least 2 foot overhangs.

If using the logs as posts, for porch or truss supports, keep the logs off the ground or concrete. This can be accomplished by using a green treated 2 x 10. Cut the 2 x 10 into a 9" diameter disc and place it on the ground, two discs may be necessary for each support. Rebar or an anchor bolt may be used to hold the disc and log in place. Tinted aluminum flashing may be wrapped around the log and the discs to hide their location.

Finishing: Caulk around all windows and doors and the corners. It is necessary to chink between the rows of logs after stacking them for a home or cabin. Do NOT seal the logs with polyurethane or varnish type sealers. Use a good quality breathable stain for maximum protection and durability.