

## **SERIES 5100**

### **PREHUNG 4-WAY UNIVERSAL SWING WALK DOOR**

#### **DOOR TYPE**

- Prehung 4-way universal swing, insulated smooth steel leaf with steel jamb and aluminum header and sill.

#### **DOOR CONSTRUCTION**

- 1-3/4" thick door pressure injected with 2.2 pounds of polyurethane foam per cubic foot.
- 24 gauge hot dipped galvanized smooth steel panels, polyester painted and baked for a durable and long lasting finish.
- Flush design - rolled edges for style, strength, and corrosion resistance.
- Polyurethane foam core for an R12 insulation value.

#### **MASTER FRAME CONSTRUCTION**

- Frame jamb is fabricated of 16 gauge steel.
- Parting stop of commercial quality aluminum extrusion 1" wide with a 0.050 min. wall thickness.
- Header and sill of commercial quality aluminum 3-1/2" wide with a 0.062 min. wall thickness.
- Frame jamb, head & sill are polyester painted and baked for a durable and long lasting appearance.
- Master frame is shipped completely assembled with hinges and door attached.
- A unique design allows the weatherstripped header parting stop to be snapped in place after the door has been installed to insure a weather tight installation.
- Sill is a low profile design, which complies with the ADA handicap accessible guidelines. It is 3-1/2" deep and 1/2" high.

#### **HARDWARE**

- Door is mounted to the frame by three, 12 gauge stainless steel, 4-1/2" x 4" fixed pin hinges.
- Door is prepped for lockset with a 2-1/8" diameter hole with a 2-3/4" backset and a 1" edge bore.
- Door panel is strengthened with an extruded aluminum reinforcing blocks at the location for entry lock, deadbolt lock, panic bar and closer.

#### **WEATHERSTRIPPING**

- Master frame is weatherstripped with a dual seal bulb and leaf of extruded Santoprene®.
- The sill sweep is a dual durometer vinyl with two flexible wands and a center bulb with a rigid base.

#### **DOOR LITES**

- 22" x 36" Insulated 9-Lite, consisting of 2 pieces of 1/8" tempered glass with a rigid aluminum grids
- All door lites are installed in pre-painted color matched extruded aluminum frames, which are foamed in place. A bonding type black bedding glazing tape provides a watertight seal and secures the glass in the opening. Glazing is completed with a snap-in dual durometer glazing bead.