Acrylic Tennis Court Crackfiller

Manufacturer:
ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477

Description
SealBest Acrylic Tennis Court Crackfiller is a 100% acrylic trowel grade crack filler designed for filling cracks in asphalt or concrete surfaces, up to 1" wide.

Uses
Asphalt or concrete tennis courts, basketball courts, play areas, and all-purpose sport surfaces.

Color
Available in green, red and neutral.

Surface Preparation
Cracks must be cleaned of dust, dirt, and debris including vegetation. Blow clean with air compressor or high pressure washer.

Mixing Procedures
Use as is. DO NOT DILUTE.

Application
Work Acrylic Crack Patch down into crack using rectangular trowel or hand held scraper. Wipe off excess material with damp cloth before it dries to prevent material buildup on court surface.
Important: Stir before using. Temperatures must be above 50°F both during application and for a period of at least 24 hours after application. Do not apply when rain is imminent or forecast. Keep from freezing. Close container when not in use.

Coverage (Approximate)
Typically one gallon will fill approximately 75-150 feet of cracks depending on depth and width of crack.

Precautions
- **Keep Out of Reach of Children**
- Do Not Freeze
- Do Not Store at Temperatures Below 50 ºF

Safety & Environmental Precautions
- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 100 gm/liter max
- KEEP OUT OF REACH OF CHILDREN

Acrylic Tennis Court Crackfiller

Revised: 07/14