Acrylic Tennis Court Coating

Manufacturer:
ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477

Description
SealBest Acrylic Tennis Court Coating is a 100% acrylic emulsion coating designed for tennis courts and other sport and recreational pavement surfaces.

Uses
Tennis courts, basketball courts, and other asphalt or concrete multi-purpose surfaces.

Color
Available in Forest Green, *Light Green, Dark Green, Beige, Brown, *Red, Maroon, Gray, and Blue.

LEED: SS Credit 7.1:
Heat Island Effect: Non-Roof
*Specific colors may contribute toward LEED credits.

Surface Preparation
Pavement surface must be cleaned entirely of dust, dirt, debris and all loose materials . Repair of pavement surface defects, depressions and cracks must be completed prior to application. All repairs must be flush and smooth to adjoining surfaces.

Mixing Procedures
Acrylic Tennis Court Coating is ready to use. Do not add water. Stir thoroughly prior to application.

Application
Apply Acrylic Tennis Court Coating with a soft rubber squeegee. Allow each coat to thoroughly dry before applying the next coat. Two coats are recommended.

Important: Stir material thoroughly before using. Temperature must be a minimum of 50° F. and rising before application. Do not apply when raining is imminent or forecast. Keep from freezing. Close container when not in use.

Coverage (Approximate)
Approximately .12 to .15 gallon per square yard per coat.

Precautions
- **Keep Out of Reach of Children**
- Do Not Freeze
- Do Not Store at Temperatures Below 50 ºF

Safety & Environmental Precautions
- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 100 gm/liter max
- KEEP OUT OF REACH OF CHILDREN

Acrylic Tennis Court Coating

Revised: 07/14