White Elastomeric Roof Coating

10 Year Protection

Manufacturer:

ThorWorks Industries, Inc.
2520 S. Campbell St.
Sandusky, OH 44870
Phone: 800-326-1994
Fax: 419-626-5477

Description

White Elastomeric Roof Coating is a 100% acrylic elastomeric rubber-like material designed to protect a variety of roof surfaces. The outstanding reflectivity will lower interior home and building temperature providing energy savings up to 35%.

Uses

A variety of roof surfaces including metal, mobile homes, aged aluminum roof coatings, concrete, campers/RV's, and more.
NOTE: This product is not recommended for gravel, dead level (flat), or shingled roof surfaces.

Surface Preparation

Clean Roof - Sweep off all dirt, dust, and debris. Remove rust, mildew, oil, grease, or other foreign material on the surface. Allow freshly applied asphalt roofs to cure a minimum of 4 weeks prior to applying this coating. Scrub roof with solution of TSP (Trisodium Phosphate) and water. Remove mold and mildew with bleach solution (1 part chlorine bleach and 3 parts water). Rinse thoroughly and allow to dry..

Application

Applying Roof Coating - Stir pail thoroughly. Do not dilute. For best results apply White Elastomeric Roof Coating with a soft brush, 3/4" nap paint roller, or high pressure sprayer. For optimum performance and durability, apply a second coat.

NOTE: This product is not recommended for gravel, dead level (flat), or shingled roof surfaces.

Clean Up

Wash tools with water before material dries.

Weather Conditions

- Application temperature must be a minimum of 60 °F and rising. Do not apply when temperature is expected to drop below 60 °F within a 24 hour period.
- In areas where dew or fog accumulates in the early evening, it is best to coat in the morning. Stop coating by early afternoon (3:00 pm) to prevent wash off, which will occur if dew, fog, or rain arrives before coating dries.
- Do not apply if rain is imminent or forecast within 24 hours of application.

Coverage (Approximate)

.9 gallons will coat approximately 50-70 square feet of roof surface.

Precautions

- Do Not Heat or Thin
- Do Not Freeze
- Do Not Store at Temperatures Below 50 ºF

Safety & Environmental Precautions

- Refer to Material Safety Data Sheet Before Using
- For Exterior Application Only
- Close Container When Not in Use
- Environmental Information is on the Material Safety Data Sheet
- Do Not Reuse Empty Container
- Volatile Organic Content (VOC) is 100 gm/liter max
- KEEP OUT OF REACH OF CHILDREN

Ingredients:	Cas No.
Water	7732-18-5
100% Acrylic Emulsion Polymer	Proprietary
Limestone	16389-88-1
Titanium Dioxide	13463-67-7
Ester Alcohol	25265-77-4

Revised: 09/16